

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : NOBO Deepclean Plus 150ml
Product code : 34538408

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Consumer use, Professional use
Use of the substance/mixture : Whiteboard Cleaner

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Acco UK Ltd.
Oxford House, Oxford Road,
Aylesbury, Bucks,
HP21 8SZ.

Telephone: +44 (0) 844 209 8360 (9am to 5pm)
Fax: +44 (0) 845 603 1731
Website: www.acco.co.uk
Email: informationeurope@acco.com

1.4. Emergency telephone number

Emergency number : 0844 2098360

Country	Organisation/Company	Address	Emergency number
IRELAND (REPUBLIC OF)	National Poisons Information Centre Beaumont Hospital	Beaumont Hospital Beaumont Road 9 Dublin	: +353 1 8379964
UNITED KINGDOM	National Poisons Information Service (NHS Direct)	http://www.npis.org	111 (England & Wales only) or 112 (EU) or 08454 24 24 24 (Scotland)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 3 H229
Acute Tox. 4 (Oral) H302

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Xn; R22

Full text of R-phrases: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS07

Signal word (CLP) :

Warning

Hazard statements (CLP) :

H229 - Pressurised container: May burst if heated
H302 - Harmful if swallowed

Precautionary statements (CLP) :

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking



NOBO Deepclean Plus 150ml Safety Data Sheet

according to Regulation (EC) No. 453/2010

P251 - Do not pierce or burn, even after use
P264 - Wash hands thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P301+P312 - IF SWALLOWED: Call a doctor if you feel unwell
P330 - Rinse mouth

2.3. Other hazards

Other hazards not contributing to the classification : Contains gas under pressure; may explode if heated.

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC
butane substance with national workplace exposure limit(s) (AT, BE, BG, DE, DK, ET, FI, FR, GB, GR, HU, IE, IT, LV, PL, PT)	(CAS No) 106-97-8 (EC no) 203-448-7 (EC index no) 601-004-00-0	1 - 15	F+; R12
sodium nitrite	(CAS No) 7632-00-0 (EC no) 231-555-9 (EC index no) 007-010-00-4	< 5	O; R8 T; R25 N; R50

Name	Product identifier	Specific concentration limits
sodium nitrite	(CAS No) 7632-00-0 (EC no) 231-555-9 (EC index no) 007-010-00-4	(1 ≤ C < 5) Xn; R22 (C ≥ 5) T; R25

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butane substance with national workplace exposure limit(s) (AT, BE, BG, DE, DK, ET, FI, FR, GB, GR, HU, IE, IT, LV, PL, PT)	(CAS No) 106-97-8 (EC no) 203-448-7 (EC index no) 601-004-00-0	1 - 15	Flam. Gas 1, H220
sodium nitrite	(CAS No) 7632-00-0 (EC no) 231-555-9 (EC index no) 007-010-00-4	< 5	Ox. Sol. 3, H272 Acute Tox. 3 (Oral), H301 Aquatic Acute 1, H400

Full text of R- and H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

First-aid measures after inhalation : Assure fresh air breathing. Allow the victim to rest.

First-aid measures after skin contact : Remove affected clothing and wash all exposed skin area with mild soap and water, followed by warm water rinse.

First-aid measures after eye contact : Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persist.

First-aid measures after ingestion : Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a POISON CENTER/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after ingestion : Swallowing a small quantity of this material will result in serious health hazard.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.

Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

No additional information available



NOBO Deepclean Plus 150ml Safety Data Sheet

according to Regulation (EC) No. 453/2010

5.3. Advice for firefighters

- Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if substance enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour.
- Hygiene measures : Do not eat, drink or smoke when using this product. Wash Skin thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep container closed when not in use. Keep only in the original container in a cool, well ventilated place away from : Direct sunlight, Heat and ignition sources.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

butane (106-97-8)		
Austria	MAK (mg/m ³)	1900 mg/m ³
Austria	MAK (ppm)	800 ppm
Austria	MAK Short time value (mg/m ³)	3800 mg/m ³
Austria	MAK Short time value (ppm)	1600 ppm
Belgium	Limit value (ppm)	1000 ppm
Bulgaria	OEL TWA (mg/m ³)	1900 mg/m ³
France	VME (mg/m ³)	1900 mg/m ³
France	VME (ppm)	800 ppm
Germany	TRGS 900 Occupational exposure limit value (mg/m ³)	2400 mg/m ³
Germany	TRGS 900 Occupational exposure limit value (ppm)	1000 ppm
Germany	Remark (TRGS 900)	DFG
Greece	OEL TWA (mg/m ³)	2350 mg/m ³
Greece	OEL TWA (ppm)	1000 ppm
Italy - Portugal - USA ACGIH	ACGIH TWA (ppm)	1000 ppm
Italy - Portugal - USA ACGIH	ACGIH STEL (ppm)	1000 ppm
Latvia	OEL TWA (mg/m ³)	300 mg/m ³
Switzerland	VME (mg/m ³)	1900 mg/m ³
Switzerland	VME (ppm)	800 ppm

NOBO Deepclean Plus 150ml Safety Data Sheet

according to Regulation (EC) No. 453/2010

butane (106-97-8)		
United Kingdom	WEL TWA (mg/m ³)	1450 mg/m ³
United Kingdom	WEL TWA (ppm)	600 ppm
United Kingdom	WEL STEL (mg/m ³)	1810 mg/m ³
United Kingdom	WEL STEL (ppm)	750 ppm
United Kingdom	Remark (WEL)	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)
Denmark	Grænseværdie (langvarig) (mg/m ³)	1200 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	500 ppm
Finland	HTP-arvo (8h) (mg/m ³)	1900 mg/m ³
Finland	HTP-arvo (8h) (ppm)	800 ppm
Finland	HTP-arvo (15 min)	2400 mg/m ³
Finland	HTP-arvo (15 min) (ppm)	1000 ppm
Hungary	AK-érték	2350 mg/m ³
Hungary	CK-érték	9400 mg/m ³
Hungary	Megjegyzések (HU)	IV.
Ireland	OEL (8 hours ref) (ppm)	1000 ppm
Norway	Gjennomsnittsverdier (AN) (mg/m ³)	600 mg/m ³
Norway	Gjennomsnittsverdier (AN) (ppm)	250 ppm
Poland	NDS (mg/m ³)	1900 mg/m ³
Poland	NDSch (mg/m ³)	3000 mg/m ³
Australia	TWA (mg/m ³)	1900 mg/m ³
Australia	TWA (ppm)	800 ppm

sodium nitrite (7632-00-0)		
Lithuania	NRV (mg/m ³)	0,1 mg/m ³
Lithuania	Remark (LT)	Ū

8.2. Exposure controls

Appropriate engineering controls : Provide adequate general and local exhaust ventilation.
 Personal protective equipment : Protective goggles. Gloves.



Hand protection : Wear protective gloves.
 Eye protection : Chemical goggles or safety glasses.
 Respiratory protection : Wear appropriate mask.
 Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
 Appearance : Aerosol.
 Colour : Colourless.
 Odour : characteristic.
 Odour threshold : No data available
 pH : 9 - 10
 Relative evaporation rate (butylacetate=1) : No data available
 Melting point : No data available
 Freezing point : No data available
 Boiling point : > 100 °C
 Flash point : No data available



NOBO Deepclean Plus 150ml Safety Data Sheet

according to Regulation (EC) No. 453/2010

Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Non flammable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Not established.

10.3. Possibility of hazardous reactions

Not established.

10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Harmful if swallowed.

NOBO Deepclean Plus 150ml	
ATE CLP (oral)	500,000 mg/kg bodyweight

butane (106-97-8)	
LC50 inhalation rat (mg/l)	658 mg/l/4h (Rat; Literature)
LC50 inhalation rat (ppm)	276000 ppm/4h (Rat; Literature)
ATE CLP (gases)	276000,000 ppmv/4h
ATE CLP (vapours)	658,000 mg/l/4h
ATE CLP (dust,mist)	658,000 mg/l/4h

sodium nitrite (7632-00-0)	
LD50 oral rat	180 mg/kg (Rat; Other; Experimental value)
LC50 inhalation rat (mg/l)	5,5 mg/l/4h (Rat; Literature study)
ATE CLP (oral)	180,000 mg/kg bodyweight
ATE CLP (vapours)	5,500 mg/l/4h
ATE CLP (dust,mist)	5,500 mg/l/4h

Skin corrosion/irritation : Not classified
Based on available data, the classification criteria are not met
pH: 9 - 10



NOBO Deepclean Plus 150ml Safety Data Sheet

according to Regulation (EC) No. 453/2010

Serious eye damage/irritation	: Not classified Based on available data, the classification criteria are not met pH: 9 - 10
Respiratory or skin sensitisation	: Not classified Based on available data, the classification criteria are not met
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified Based on available data, the classification criteria are not met
Reproductive toxicity	: Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity (repeated exposure)	: Not classified Based on available data, the classification criteria are not met
Aspiration hazard	: Not classified Based on available data, the classification criteria are not met
Potential adverse human health effects and symptoms	: Harmful if swallowed.

SECTION 12: Ecological information

12.1. Toxicity

butane (106-97-8)	
LC50 fishes 1	> 1000 mg/l (96 h; Pimephales promelas)
LC50 fish 2	6,0 mg/l (96 h; Pisces)
TLM fish 1	1000 mg/l (96 h; Pisces)
Threshold limit other aquatic organisms 1	0.6 - 0.9,504 h; Daphnia magna
Threshold limit algae 1	0.88 - 1.76,Algae
sodium nitrite (7632-00-0)	
LC50 fishes 1	40,6 mg/l (96 h; Channa punctatus; Nitrite)
EC50 Daphnia 1	12,5 - 100 mg/l (48 h; Daphnia magna; Nitrite)
EC50 other aquatic organisms 1	20 mg/l (Protozoa; Toxicity test)
LC50 fish 2	0,56 - 1,78 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 2	66 mg/l (48 h; Daphnia magna; Nitrogen)
TLM fish 1	7,5 ppm (48 h; Gambusia affinis)
Threshold limit algae 1	1230 mg/l (192 h; Scenedesmus quadricauda; Nitrite)
Threshold limit algae 2	350 mg/l (192 h; Microcystis aeruginosa; Nitrite)

12.2. Persistence and degradability

NOBO Deepclean Plus 150ml	
Persistence and degradability	Not established.
butane (106-97-8)	
Persistence and degradability	Readily biodegradable in water.
sodium nitrite (7632-00-0)	
Persistence and degradability	Biodegradable in water. Autooxidation in water. No (test)data available on mobility of the substance.

12.3. Bioaccumulative potential

NOBO Deepclean Plus 150ml	
Bioaccumulative potential	Not established.
butane (106-97-8)	
Log Pow	2,89 (Experimental value)
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).

sodium nitrite (7632-00-0)	
BCF fish 1	11,3 Salmo gairdneri (Oncorhynchus mykiss)
Log Pow	-3,7 (Experimental value; OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 25 °C)
Bioaccumulative potential	Low bioaccumulation potential (Log Kow < 4).

12.4. Mobility in soil

butane (106-97-8)	
Surface tension	< 0,1 N/m (0 °C)

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

Other information : Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to a licensed waste centre in accordance with local/regional/national/international regulations.

Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

14.1. UN number

UN-No. (ADR) : 1950

14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS
Transport document description (ADR) : UN 1950 AEROSOLS, 2.1, (D)

14.3. Transport hazard class(es)

Class (ADR) : 2
Hazard labels (ADR) : 2.1



14.4. Packing group

Not applicable

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Special precautions for user

14.6.1. Overland transport

Classification code (ADR) : 5F
Special provisions (ADR) : 190, 327, 344, 625
Transport category (ADR) : 2
Tunnel restriction code (ADR) : D
Limited quantities (ADR) : 1L
Excepted quantities (ADR) : E0

14.6.2. Transport by sea

No additional information available

14.6.3. Air transport

No additional information available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

The following restrictions are applicable according to Annex XVII of the REACH Regulation (EC) No 1907/2006:

3. Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008	NOBO Deepclean Plus 150ml
3.a. Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8 types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F	butane
40. Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or not.	butane

Contains no substance on the REACH candidate list

15.1.2. National regulations

Water hazard class (WGK) : nwg - non-hazardous to water
 WGK remark : No water pollutant (Classification based on the components in compliance with Verwaltungsvorschrift wassergefährdender).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of R-, H- and EUH-phrases:

Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aerosol 3	Aerosol, Category 3
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Flam. Gas 1	Flammable gases, Category 1
Ox. Sol. 3	Oxidising Solids, Category 3
H220	Extremely flammable gas
H229	Pressurised container: May burst if heated
H272	May intensify fire; oxidiser
H301	Toxic if swallowed
H302	Harmful if swallowed
H400	Very toxic to aquatic life
R12	Extremely flammable
R22	Harmful if swallowed
R25	Toxic if swallowed
R50	Very toxic to aquatic organisms
R8	Contact with combustible material may cause fire
F+	Extremely flammable
N	Dangerous for the environment
O	Oxidising
T	Toxic
Xn	Harmful

SDS EU ACCO

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product